

INT-SF-WSW

PARTITION KEYPAD

The **INT-SF-WSW** partition keypad allows you to control operation of each alarm system based on the control panels of **INTEGRA** and **INTEGRA Plus** families. To maintain a uniform design line of the controls, it is recommended that the INT-SF partition keypad be used in alarm systems including the **INT-KLFR**, **INT-TSI**, **INT-TSG** and **INT-KSG** keypads.

- white color backlight
- controls single partition in the system
- PANIC, FIRE and AUX alarms triggered from keypad
- LEDs for partition status indication
- buzzer for acoustic signaling of selected system events
- access control functions
- relay for electromagnetic lock / electric strike control
- door status monitoring input
- available in white (**INT-SF-W**), black (**INT-SF-B**), light with silver frame (**INT-SF-SSW**), dark with silver frame (**INT-SF-BSB**) and white with silver frame (**INT-SF-WSW**)



TECHNICAL DATA

Supply voltage	12 V DC
Operating temperature range	-10 °C...+55 °C
Standby mode current consumption	20 mA
Max. current consumption	40 mA
Weight	180 g
Maximum humidity	93±3%
Dimensions	80 x 143 x 25 mm
Environmental class according to EN50130-5	II
Relay output rating (resistive load)	1 A / 30 V DC

