

BRACKET C GY

SET OF WALL BRACKETS FOR MOUNTING SATEL OUTDOOR DETECTORS (GREY)

The **BRACKET C** set of wall brackets is designed for mounting the **OPAL**-series and **AOD-210** outdoor motion detectors. The set consists of two brackets: ball-joint and angled, making it easier to find the optimal position relative to the detection zone.

Each of the brackets is also provided with a tamper switch responding to any attempt to pull the device away from the wall.

Angle type bracket:

- for mounting on a flat surface (rectangular pillar, wall, inside corner of two walls)
- tilt angle between detector base and bracket mounting surface: 45°
- tamper element breaking off at an attempt to detach the bracket from the wall

Ball-joint swivel type bracket:

- for mounting on a flat surface (rectangular pillar, wall)
- angle between detector base and bracket mounting surface adjustable horizontally through 90° (+/- 45°)
- angle between detector base and bracket mounting surface adjustable vertically through 60° (+/- 30°)
- tamper switch which responds to an attempt to pull the bracket away from wall, complete with 3 wires for connecting it to the NC or NO type circuit



BRACKET C GY is also available in colours: white **BRACKET C**, dedicated for **OPAL**, **OPAL Plus**, **OPAL Pro** and **AOD-210**, and dark grey **BRACKET C DG**, dedicated for detectors with **OPC-3 DG** enclosure.

BRACKET C GY can be expanded with components of the **BRACKET E GY** distance bracket:

- **BRACKET E-1 GY** - Body
- **BRACKET E-2B GY** - Insert for the OPAL/AOD-210 outdoor detectors
- **BRACKET E-3 GY** - Spacer (height 30 mm)
- **BRACKET E-6 GY** - Tamper sensor (1 NO/NC switch, 50 cm cable length)

Open the compatybility table