

ASW-200 E

SMART PLUG WITH TYPE E SOCKET (EURO)

ASW-200 E is a smart plug that allows to remotely turn on and off connected devices. The smart plug is designed to work within a two-way wireless **ABAX 2** system.

- control of electrical devices of up to 2300 W
- encrypted two-way radio communication in the 868 MHz frequency band (AES standard)
- diversification of transmission channels – 4 channels allow automatic selection of one that guarantees transmission without interference with other signals in the 868 MHz frequency band
- remote upgrade of the smart plug firmware
- remote configuration
- LED indicator
 - can display current consumption by the connected device
 - alerts of failure
 - can turn the indicator off completely
 - special button for configuring the indicator settings
- firmware protection against overloading and overheating



ASW-200 is controlled by*:

- **ACU-220** and **ACU-280** system controllers
- **BE WAVE Hybrid** control panels
- **BE WAVE Smart HUB** controllers
- **ARU-200** radio signal repeater

ASW-200 is also available with Type **F** socket (SCHUKO).

**detailed data available in the device manual*

TECHNICAL DATA

Operating temperature range	-10°C...+55°C
Weight	60 g
Maximum humidity	93±3%
Operating frequency band	868,0 ÷ 868,6 MHz
Dimensions	ø45 x 67 mm
Environmental class according to EN50130-5	II
Complied with standards	EN 50130-4, EN 50130-5
Maximum power consumption	1,37 W
Radio communication range (in open area) for ABAX	up to 500 m
Rated current (resistive load)	10 A
Radio communication range (in open area) for ABAX 2	up to 1000 m
Standby power consumption	0,73 W
Supply voltage	230 V AC, 50 Hz



The actual appearance of the products may differ from the presented images. Product descriptions are provided in the web service for information purposes only.