

SPW-210 R

INDOOR SIREN WITH ACOUSTICAL SIGNALING

SPW-210 R is a siren with acoustic signaling, designed for indoor installation and provided with piezoelectric transducer. There are three types of modulated tones with 120 dB intensity to choose from. The loud signal ensures good audibility over a large area, e.g. in warehouses, production halls, parking lots inside buildings, etc. Enclosure of the siren is made of polycarbonate, thus ensuring high mechanical strength and aesthetic appearance of the device that remains unchanged over time. The siren is provided with tamper protection against opening or tearing off the wall. This model complies with the EN 50131-1 requirements for Grade 2 security.

The SPW-210 acoustic siren is available in two color versions: SPW-210 R (red) and SPW-210 BL (blue).

- acoustical signaling: piezo transducer
- tamper protection against opening and removing from mounting surface
- available also in blue (**SPW-210 BL**)



TECHNICAL DATA

| | |
|-----------------------------|------------------|
| Environmental class | II |
| Supply voltage | 12 V DC |
| Enclosure dimensions | 87 x 133 x 37 mm |
| Operating temperature range | -10...+55 °C |
| Max. current consumption | 110 mA |
| Weight | 159 g |
| The intensity of sound | 120 dB |



The actual appearance of the products may differ from the presented images. Product descriptions are provided in the web service for information purposes only.