

SPL-2030 R

OUTDOOR SIREN WITH OPTICAL AND ACOUSTICAL SIGNALING

SPL-2030 is an optical-acoustic siren designed for outdoor installation, provided with super bright LEDs and a piezoelectric transducer. It offers three types of 120 dB intensity modulated tones to choose from. Enclosure of the siren is made of polycarbonate, which ensures high mechanical strength and aesthetic appearance of the device that remains unchanged over time. The device is provided with tamper protection against opening or tearing off the wall. The SPL-2030 R model can be additionally provided with the SPL-TO sensor for protection against damping the siren by covering the piezoelectric transducer with PUR foam. Optionally, an inner shield of galvanized sheet is available to protect the electronics board and transducer against mechanical damage. The electronic circuits are properly weatherproofed, so they are also resistant to the effects of harsh environmental conditions.

The SPL-2030 optical-acoustic siren is available in two color versions: SPL-2030 R (red) and SPL-2030 BL (blue).

- acoustical signaling: piezo transducer
- optical signaling: ultra bright LEDs
- tamper protection against:
 - optional anti-foam tamper (standard or optical – **SPL-TO**)
 - opening
 - removing from mounting surface
- available also in blue (**SPL-2030 BL**)

TECHNICAL DATA

Environmental class	III
Enclosure dimensions	298 x 197 x 90 mm
Operating temperature range	-35...+55 °C
Nominal supply voltage (±15%)	12 V DC
Average current consumption (acoustic signaling)	250 mA
Average current consumption (optical signaling)	35 mA
Weight	725 g
The intensity of sound	120 dB

